



IP7142

Fixed Network Camera

WDR • Outdoor • Day&Night

VIVOTEK IP7142 network camera features a WDR (Wide Dynamic Range) CMOS sensor to cope with any challenging lighting conditions. This function enables IP7142 to be largely applied in highly contrast environments such as lobby entrances, parking lots, ATM, loading areas and much more.

The WDR feature captures both of the dark part and bright part and combining the differences into a scene to generate a highly realistic image as original scene. Therefore, IP7142 can provide video quality closer to the capabilities of the human eye. The day and night function and the IP66-rated integrated housing of IP7142 enable users to easily build up a cost-effective IP surveillance system without additional accessories. Incorporating an IR-cut filter that can be removed automatically at night and built-in IR illuminators with coverage for up to 15 meters, IP7142 is an outstanding 24-hour surveillance solution. Meanwhile, the IP66-rated integrated housing shields this camera from dust and water, allowing it to be applied in harsh weather conditions of outdoor environments.

Other advanced features of IP7142 include simultaneous dual streams, 3GPP mobile surveillance, 802.3af compliant PoE, two-way audio by SIP protocol, RS-485 interface for scanners or pan/tilts driver connection, and HTTPS encrypted data transmission.

Features

- > Wide Dynamic Range CMOS Sensor
- > 3.3~12mm Vari-focal Board Lens
- > Removable IR-cut Filter for Day & Night Function
- > Built-in IR Illuminators, effective up to 15 Meters
- > Weather-proof IP66-rated Housing
- > Real-time MPEG-4 and MJPEG Compression (Dual Codec)
- > Supports Dual Streams Simultaneously
- > Built-in 802.3af Compliant PoE
- > Two-way Audio via SIP Protocol
- > Digital I/O for External Sensor and Alarm
- > RS-485 Interface for Scanners, Pan/Tilts

Specifications

System	<ul style="list-style-type: none"> CPU: VTK-1000 SoC Flash: 8MB RAM: 64MB Embedded OS: Linux 2.4 	Housing	<ul style="list-style-type: none"> Weather-proof IP66-rated housing
Lens	<ul style="list-style-type: none"> Board lens, vari-focal, f=3.3 ~ 12 mm, F1.4 (wide), F2.9 (tele), focus range: 50 cm to infinity Removable IR-cut filter for day & night function 	Approvals	<ul style="list-style-type: none"> CE, LVD, FCC, VCCI, C-Tick
Angle of View	<ul style="list-style-type: none"> 23.9° ~ 89.8° (horizontal) 17.9° ~ 63.6° (vertical) 	Operating Environments	<ul style="list-style-type: none"> Temperature: -20 ~ 60 °C (-4 ~ 140 °F) Humidity: 20% ~ 80% RH
Shutter Time	<ul style="list-style-type: none"> 1/30 sec. to 1/15000 sec. 	Viewing System Requirements	<ul style="list-style-type: none"> OS: Microsoft Windows 2000/XP/Vista Browser: Internet Explorer 6.x or above Cell phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.5 or above
Image Sensor	<ul style="list-style-type: none"> 1/3.3" Wide Dynamic Range CMOS sensor in 720x480 resolution 	Installation, Management, and Maintenance	<ul style="list-style-type: none"> Installation Wizard 2 16-CH recording software Supports firmware upgrade
Minimum Illumination	<ul style="list-style-type: none"> 0.68 Lux / F1.4 0 Lux / F1.4 (IR LED on) 	Applications	<ul style="list-style-type: none"> SDK available for application development and system integration
IR Illuminators	<ul style="list-style-type: none"> IR LED x 12 (850 nm) Effective up to 15 meters 	Warranty	<ul style="list-style-type: none"> 24 months
Video	<ul style="list-style-type: none"> Compression: MJPEG & MPEG-4 Streaming: <ul style="list-style-type: none"> Simultaneous dual-streaming MPEG-4 streaming over UDP, TCP, or HTTP MPEG-4 multicast streaming MJPEG streaming over HTTP Supports 3GPP mobile surveillance Frame rates: <ul style="list-style-type: none"> MPEG-4: Up to 25 fps at 720x480 MJPEG: Up to 25 fps at 720x480 	System Overview	
Image Settings	<ul style="list-style-type: none"> Adjustable image size, quality, and bit rate Time stamp and text caption overlay Flip & mirror Configurable brightness, contrast, saturation, and hue AGC, AWB, AEC (Automatic Exposure Control), WDR Automatic or manual day/night mode Supports privacy masks 		
Audio	<ul style="list-style-type: none"> Compression: <ul style="list-style-type: none"> GSM-AMR speech encoding, bit rate: 4.75 kbps to 12.2 kbps MPEG-4 AAC audio encoding, bit rate: 16 kbps to 128 kbps Interface: <ul style="list-style-type: none"> External microphone input Audio output Supports two-way audio via SIP protocol Supports audio mute 	External View	
Networking	<ul style="list-style-type: none"> 10/100 Mbps Ethernet, RJ-45 Protocols: IPv4, TCP/IP, HTTP, UPnP, RTSP/ RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, and PPPoE 		
Alarm and Event Management	<ul style="list-style-type: none"> Triple-window video motion detection One D/I and one D/O for external sensor and alarm Event notification using HTTP, SMTP, or FTP Local recording of MP4 file 		
Security	<ul style="list-style-type: none"> Multi-level user access with password protection IP address filtering 		
Users	<ul style="list-style-type: none"> Camera live viewing for up to 10 clients 		
Dimension	<ul style="list-style-type: none"> Ø 70 mm x 182 mm 		
Weight	<ul style="list-style-type: none"> Net: 969 g 		
LED Indicator	<ul style="list-style-type: none"> System restore status indicator 		
Power	<ul style="list-style-type: none"> 12V DC 24V AC Power consumption: Max. 6 W 802.3af compliant Power-over-Ethernet 		

All specifications are subject to change without notice. Copyright©2009 VIVOTEK INC. All rights reserved.

Distributed by:



Taching Electronic Snd. Bhd.

2-68A (2nd Flr) & 4-16 (4th Flr), Plaza LowYat, Off Jalan Bukit Bintang, 55100 Kuala Lumpur, Malaysia

Tel: +603-2711 7112

Fax: +603-2148 9110

Email: info@pocketnetcam.com